


## CABLE CONSTRUCCIÓN COMÚN

Cable 6x37 + 1


Diámetro	Peso (kg/m)	Alma Textil		Alma Acero	
		Carga rotura efect.min. (kg)	Carga rotura efect.min. (kg)		
6 mm	0.16	2450	3080		
8 mm	0.24	3860	4160		
9.50 mm	0.35	5530	5950		
11 mm	0.48	7500	8070		
13 mm	0.63	9100	10400		
14 mm	0.79	12200	13200		
16 mm	0.98	15100	16200		
19 mm	1.47	21600	23200		
22 mm	1.92	29600	31400		
26 mm	2.50	37900	40700		



## CABLE CONSTRUCCIÓN COMÚN

Cable 6x19 + 1

Diámetro	Peso (kg/m)	Alma Textil		Alma Acero	
		Carga rotura efect.min. (kg)	Carga rotura efect.min. (kg)		
3 mm	0.033	415	475		
4 mm	0.058	740	845		
5 mm	0.091	1160	1320		
6 mm	0.130	1670	1910		
8 mm	0.233	2960	3390		
10 mm	0.372	4630	5290		
11 mm	0.450	5610	6410		
12 mm	0.536	6670	7620		
13 mm	0.630	7830	8950		
14 mm	0.730	9080	10400		



## CABLE CONSTRUCCIÓN COMÚN

Cable 6x7 + 1

Diámetro	Peso (kg/m)	Alma Textil	
		Carga rotura efect.min. (kg)	
2 mm	0.014	215	
2,5 mm	0.022	335	
3 mm	0.031	480	
4 mm	0.056	850	
5 mm	0.087	1330	
6 mm	0.126	1910	
8 mm	0.223	3400	
10 mm	0.357	5320	
11 mm	0.432	6430	
12 mm	0.515	7650	
13 mm	0.604	8980	
14 mm	0.700	10400	
16 mm	0.915	13600	
19 mm	1290	19200	
22 mm	1730	25750	